

# SCHULTE®

## 9600F SNOW BLOWER



### 96" Cutting Width Front Mount Frame Comfort & Convenience



- 1** The 30" four paddle fan has a unique open centre, cupped blade design that concentrates the snow to the centre of the fan for improved snow throwing distance.
- 2** Heavily reinforced auger matched with high efficient fan feeds snow to the fan and ensures that chunks of ice and hard packed snow are broken up before being discharged.
- 3** The frame can be telescoped up to 45" to accommodate tractors of different lengths, and the new frame design transfers loads to the tractor draw bar.
- 4** The new frame mount design allows the blower head to be lifted up to 17" off the ground.

G O N U M B E R O N E . . . G O S C H U L T E !

# 96" Cutting Width Front Mount Frame Comfort & Convenience

## SPECIFICATIONS

|  |                            |
|--|----------------------------|
| Cutting width                                | <b>96" (2.44m)</b>         |
| Tractor horsepower                           | <b>85-140hp (63-104KW)</b> |
| Cutting height                               | <b>35" (889mm)</b>         |
| Overall height                               | <b>82" (2.08m)</b>         |
| Auger diameter                               | <b>23" (584mm)</b>         |
| Fan diameter                                 | <b>30" (762mm)</b>         |
| Fan type                                     | <b>4 paddle</b>            |
| Auger drive chain                            | <b>#80</b>                 |
| Weight (approximate)                         | <b>2370lbs. (1077kg)</b>   |
| Tractor PTO speed                            | <b>1000RPM</b>             |
| Adjustable skid shoes                        | <b>standard</b>            |
| Replaceable cutting blade                    | <b>standard</b>            |
| Adjustable chute deflector                   | <b>standard</b>            |
| Heavy duty chute                             | <b>standard</b>            |
| Hydraulic chute rotator mechanism & cylinder | <b>standard</b>            |
| Hydraulic lift cylinders                     | <b>standard</b>            |
| Heavy duty telescoping frame                 | <b>standard</b>            |
| 1000RPM all gear drive                       | <b>standard</b>            |



**A large gear driven parallel shaft gearbox reduces drive speed so that the main shaft runs at 540RPM.**

**An easily accessible shear pin, located on the tractor power shaft, protects the drive line from shock loads.**

**Heavy duty chute kit allows the deflector mechanism to be operated hydraulically.**

**220 chute rotation mechanism comes with 8" stroke hydraulic cylinder.**

## OPTIONS

1. Truck loading chute
2. Hydraulic chute deflector kit
3. Tractor mounting kit



Schulte Industries Ltd. reserves the right to change the design, material and specifications of its products without notice. Illustrations may include optional equipment and accessories, and may not include all standard equipment. Part No. 1000-160

**Sold By:**

# SCHULTE®



**Schulte Industries Ltd.,**  
P.O. Box 70, Englefeld Saskatchewan, Canada S0K 1N0  
Tel: (306) 287-3715 Fax: (306) 287-3355  
E-Mail: [info@schulte.ca](mailto:info@schulte.ca)  
Visit our Web site at: [www.schulte.ca](http://www.schulte.ca)